




## RUIZUAN PCD DIE BLANKS AVAILABLE SIZES


### 1. CDH: Self-supported Hexagonal shape PCD Die Blanks

RUIZUAN CODE	ADDMA CODE	Dimensions (mm)			Max. Hole Diameter (mm)	Grain Size (μm)				
		D	d	T		3	5	10	25	50
CDH2010	\	-	2.0	1.0	-	○	●	●	●	●
CDH2510	D6	-	2.5	1.0	0.4	○	●	●	●	●
CDH3215	D12	-	3.2	1.5	1.0	○	●	●	●	●
CDH4020	\	-	4.0	2.0	1.3	○	●	●	●	●
CDH4725	\	-	4.7	2.5	1.4	○	●	●	●	●
CDH5225	D15	-	5.2	2.5	1.5	○	●	●	●	●
CDH5235	D18	-	5.2	3.5	2.0	○	●	●	●	●
CDH6040	\	-	6.0	4.0	2.5	○	●	●	●	●



### 2. CDR: Self-supported Round Shape PCD Die Blanks

CODE	ADDMA CODE	Dimensions (mm)			Max. Hole Diameter (mm)	Grain Size (μm)				
		D	d	T		3	5	10	25	50
CDR2510	\	-	2.5	1.0	0.4	○	●	●	●	●
CDR3110	D6	-	3.1	1.0	0.5	○	●	●	●	●
CDR3115	D12	-	3.1	1.5	1.0	○	●	●	●	●
CDR4020	\	-	4.0	2.0	1.3	○	●	●	●	●
CDR5225	D15	-	5.2	2.5	1.5	○	●	●	●	●
CDR5235	D18	-	5.2	3.5	2.0	○	●	●	●	●
CDR8040	D21	-	8.0	4.0	3.0	○	●	●	●	●
CDR9853	D24	-	9.8	5.3	4.0	○	●	●	●	●






# Zhengzhou Ruizuan Diamond Tool Co., Ltd.

A6-3-3101, Happiness Harbor, South Chengdong Road, Zhengzhou, Henan, China. 450000  
 Website: [www.pcd-diamond.com](http://www.pcd-diamond.com) E-mail: [sales@pcd-diamond.com](mailto:sales@pcd-diamond.com)  
 Tel: +86-371- 55909782 Fax: +86-371-55909782

## 3. RSP:Tungsten Carbide Supported PCD Die Blanks

CODE	ADDMA CODE	Dimensions (mm)			Max. Hole Diameter (mm)	Grain Size (μm)				
		D	d	T		3	5	10	25	50
RSP415	D12	8.12	4.0	1.5	1.0	○	●	●	●	●
RSP423	D15	8.12	4.0	2.3	1.8	○	●	●	●	●
RSP429	D18	8.12	4.0	2.9	2.3	○	●	●	●	●
RSP740	D21	13.65	7.0	4.0	3.5	○	●	●	●	●
RSP753	D24	13.65	7.0	5.3	4.6	○	●	●	●	●
RSP13085	D27	24.13	13.0	8.5	5.8	-	-	●	●	●
RSP130115	D30	24.13	13.0	11.5	7.6	-	-	●	●	●



### Remark:

1. “●” means available, “○” means not available.
2. ADDMA Code is designed by American Diamond Die Manufacturers Association.
3. Non-standard products can be available, please inquiry if you have.
4. Max hole diameter is recommend for soft nonferrous wire. For hard wire drawing, normally it should not exceed 65% of this diameter.
5. Ruizuan PCD Die Blanks should be cased below 650℃.